

HYDROCARBON CONTAINER LEASING

PORTABLE CRYOGENIC ISO CONTAINER SERVICE:

Maximum D.O.T. Fill Capacity Various Gases based on 24,900 liter ISO Capacity:

<u>Product / DOT fill density %</u>	<u>lbs. / gallon</u>	<u>Max. gallons / ISO</u>	<u>Approx. lbs. / ISO</u>
n-Butane (all grades)	51 % 4.865 lbs.	5,753 net gallons	27,990 net lbs.
Butene-1 (all grades)	54 % 5.004 lbs.	5,922 net gallons	29,635 net lbs.
Isobutane (all grades)	49 % 4.686 lbs.	5,739 net gallons	26,891 net lbs.
Isobutylene (all grades)	53 % 4.996 lbs.	5,822 net gallons	29,086 net lbs.
Propane (all grades)	42 % 4.22 lbs.	5,462 net gallons	23,050 net lbs.
Propylene (all grades)	44 % 4.343 lbs.	5,560 net gallons	24,147 net lbs.
n-Pentane (all grades)	56 % 5.255 lbs.	5,848 net gallons	30,737 net lbs.
Isopentane (all grades)	56 % 5.194 lbs.	5,917 net gallons	30,733 net lbs.

