

Page: 1 of 6
Printed: 03/29/2015
Revision: 02/08/2022

Supersedes Revision: 03/23/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: 00003
Product Name: Propane

Company Name: Gas Innovations Phone Number:

18005 E. Hwy 225 +1 (281)471-2200

La Porte, TX 77571

Web site address: www.gasinnovations.com

Emergency Contact: 3E (within United States) +1 (866)303-2640 **Information:** Infotrac (outside of United States) +1 (352)323-3500

Synonyms: R-290

2. HAZARDS IDENTIFICATION

Flammable Gases, Category 1
Gas Under Pressure, Compressed gas





GHS Signal Word: Danger

GHS Hazard Phrases: H220 - Extremely flammable gas.

H280 - Containers gas under pressure; may explode if heated.

GHS Precaution Phrases: P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

GHS Response Phrases: P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - Eliminate all ignition sources if safe to do so.

GHS Storage and Disposal

Phrases:

P410+403 - Protect from sunlight and store in well-ventilated place.

Hazard Rating System:



Potential Health Effects (Acute and Chronic):

Propane is nontoxic but can act as a simple asphyxiant by displacing air. Symptoms of asphyxia include rapid respirations, dizziness and fatigue. Contact with the liquid phase

or with the cold gas escaping from cylinder may cause frostbite.

Inhalation: May be harmful if inhaled. May cause respiratory tract irritation. Propane is nontoxic but

can act as a simple asphyxiant by displacing air.

Skin Contact: May be harmful if absorbed through the skin. May cause skin irritation.

Eye Contact: May cause eye irritation.

Ingestion: May be harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # Hazardous Components (Chemical Name) Concentration

74-98-6 Propane 100 %



Page: 2 of 6 Printed: 03/29/2015 Revision: 02/08/2022

Supersedes Revision: 03/23/2015

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of

dangerous area.

In Case of Inhalation: If breathed in, move person into fresh air. If not breathing give artificial respiration,

preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

In Case of Skin Contact: Wash off with soap and plenty of water. If skin irritation occurs, get medical

advice/attention.

In Case of Eye Contact: Immediately flush eyes with plenty of water for at I east 15 minutes. Hold eyelids apart

and flush eyes with plenty of water. After initial flushings, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by

medical personnel.

In Case of Ingestion: Not expected to be a primary route of exposure.

5. FIRE FIGHTING MEASURES

Flash Pt: NA Method Used: Not Applicable

Explosive Limits: LEL: 2.2 %(V) UEL: 9.5 %(V)

Autoignition Pt: 468 C (874 F)

Suitable Extinguishing Media: Stop the flow of gas. IF the flow cannot be stopped, let the fire burn out while cooling the

cylinder and the surrounding areas using a water spray.

Fire Fighting Instructions: Personnel may have to wear approach-type protective suits and positive pressure

self-contained breathing apparatus. Firefighters' turnout gear may be inadequate. Cylinders exposed to fire may rupture with violent force. Extinguishing surrounding fire and keep cylinders cool by applying water from a maximum possible distance with a water spray. Flammable gases may spread from a spill after the fire is extinguished and

be subject to re-ignition.

Flammable Properties and

Hazards:

High temperatures and fire conditions can result in the formation of carbon monoxide

and carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Protective Precautions, Protective Equipment and Emergency Procedures: Use proper personal protective equipment as indicated in Section 8.

Environmental Precautions: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Steps To Be Taken In Case Material Is Released Or Spilled: Forms explosive mixtures with air. Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Remove all sources of ignition if safe to do so. Reduce vapors with fog or fine water spray, taking care not to spread liquid with water. Shut off flow if safe to do so. Ventilate area or move container to a well-ventilated area. Flammable vapors may spread from leak and could explode if reignited by sparks or flames. Explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with an appropriate device.

For controlling larger flows, personnel may have to wear approach-type protective suits

and self-contained breathing apparatus.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Avoid inhalation of vapor or mist. Keep away from heat, sparks and flame. Keep away from sources of ignition - No smoking. Use spark-proof tools and explosion proof equipment. Use in a closed system. Secure the cylinder to prevent it from falling or being knocked over. Leak check the lines and equipment. Have an emergency plan covering steps to be taken in the event of an accidental release.



Page: 3 of 6 Printed: 03/29/2015 Revision: 02/08/2022

Supersedes Revision: 03/23/2015

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents.

Precautions To Be Taken in

Storing:

Other Precautions:

Cylinders should be stored and used in dry, well-ventilated areas away from sources of heat or ignition. Store away from oxidizers.

When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS# **Partial Chemical Name OSHA TWA ACGIH TWA Other Limits** PEL: 1000 ppm No data.

TLV: (2500 ppm) 74-98-6 Propane

Respiratory Equipment

(Specify Type):

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA

approved respiratory protection should be worn.

Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield **Eye Protection:**

during cylinder change out or whenever contact with product is possible. Select eye

protection in accordance with OSHA 29 CFR 1910.133.

Protective Gloves: Wear appropriate gloves to prevent skin exposure.

Not required under normal use conditions. Other Protective Clothing:

Engineering Controls

(Ventilation etc.):

Work/Hygienic/Maintenance

Practices:

Use explosion-proof ventilation equipment. Facilities storing or utilizing this material

should be equipped with an eyewash facility, and a safety shower is recommended.

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately

after handling the product.



Page: 4 of 6 Printed: 03/29/2015 Revision: 02/08/2022

Supersedes Revision: 03/23/2015

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [X] Gas [] Liquid [] Solid

Appearance and Odor: Appearance: colorless.

Odor: Characteristic natural gas odor.

Specific Volume: 0.531 m3/kg, 8.5 ft3/lb @ 1 atm, 21.1C.

Solubility in Water: 6.5 cm3/0.1 kg water @ 1 atm, 18C.

Freezing Point: -188 C (-306 F) **Boiling Point:** -42.1 C (-43.8 F)

Decomposition Temperature: NA

Autoignition Pt: 468 C (874 F)

Flash Pt: NA Method Used: Not Applicable **Explosive Limits:** LEL: 2.2 %(V) UEL: 9.5 %(V)

Specific Gravity (Water = 1): NA

Density: 1.55 @ 1 atm at 20.0 C (68.0 F)

Bulk density: NA

Vapor Pressure (vs. Air or

109 PSI at 21.1 C (70.0 F)

mm Hg):

NA Vapor Density (vs. Air = 1): NA **Evaporation Rate:** Solubility in Water: NA **Saturated Vapor** NA

Concentration:

NA Viscosity: NA pH: **Percent Volatile:** NA **VOC / Volume:** NA Particle Size: NA NA **Heat Value: Corrosion Rate:** NA

Molecular Formula & Weight: C3H8 44.097

10. STABILITY AND REACTIVITY

High temperatures and fire conditions can result in the formation of carbon monoxide Reactivity:

and carbon dioxide.

Unstable [] Stable [X] Stability:

Conditions To Avoid -Heat, flames and sparks. No smoking.

Instability:

Incompatibility - Materials To Oxidizing materials.

Hazardous Decomposition Or High temperatures and fire conditions can result in the formation of carbon monoxide

and carbon dioxide. **Byproducts:**

Will occur [] Possibility of Hazardous

Reactions:

Will not occur [X]

Conditions To Avoid -No data available.

Hazardous Reactions:



Page: 5 of 6 Printed: 03/29/2015

Revision: 02/08/2022

Supersedes Revision: 03/23/2015

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Acute toxicity: No data available.

Epidemiology: No information available. Teratogenicity: No information available. Reproductive Effects: No information available.

Mutagenicity: No information available. Neurotoxicity: No information available.

Irritation or Corrosion: No data available.

Sensitization: No data available.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. ECOLOGICAL INFORMATION

General Ecological Environmental: No information available. **Information:** Physical: No information available.

Results of PBT and vPvB

assessment:

No data available.

Persistence and

No data available.

Degradability:

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Do not attempt to dispose of residual or unused quantities. Return container to supplier.

Dispose of contents/containers in accordance with local/regional/national/international

regulations.

14. TRANSPORT INFORMATION

TRANSPORTATION DOCUMENT DESCRIPTION: UN1978 Propane (see also Petroleum gases, liquefied (UN1075). 2.1

DOT Proper Shipping Name: Propane. see also Petroleum gases, liquefied (UN1075).

DOT Hazard Class: 2.1 FLAMMABLE GAS

UN/NA Number: UN1978

DOT Special Provisions (49 CFR172.102)

FLAMMABLE GAS
2

For domestic transportation only, the identification number UN1075 may be used in place of the identification number specified in column (4) of the 172.101 table. The identification number used must be consistent on package markings, shipping papers and emergency response information.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS # Hazardous Components (Chemical Name) S. 302 (EHS) S. 304 RQ S. 313 (TRI)

74-98-6 Propane No No No

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

74-98-6 Propane TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8:

No; MA Oil/HazMat: Yes; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 1594; NY Part 597: No; PA HSL: Yes - 1; SC

TAP: No; WI Air: No

CAS # Hazardous Components (Chemical Name) International Regulatory Lists

74-98-6 Propane Canadian DSL: Yes; Canadian NDSL: No; Mexico INSQ: Yes -

1075; Australia ICS: Yes; New Zealand IOC: Yes; China IECSC: Yes; Japan ENCS: Yes - (2)-3; Korea ECL: Yes -



Page: 6 of 6 Printed: 03/29/2015 Revision: 02/08/2022

Supersedes Revision: 03/23/2015

KE-29258; Philippines ICCS: Yes; REACH: Yes - (R), (P)

16. OTHER INFORMATION

Revision Date: 03/23/2015

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information, recommendations, and suggestions herein were compiled from reference material and other sources believed to be reliable. However, the SDS's accuracy or completeness is not guaranteed by Gas Innovations or its affiliates, nor is any responsibility assumed or implied for any loss or damage resulting from inaccuracies or omissions. Since conditions of use are beyond our control, no warranties of merchantability of fitness for a particular purpose are expressed or implied. This SDS is not intended as a license to operate under, or a recommendation to infringe on, any patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.